




GRABO Version Comparison Chart

			
Model	NEMO GRABO	GRABO PRO-LIFTER 20	GRABO H
FUNCTIONAL PARAMETERS			
Battery	14.8VDC 2600mAh Li-ion	14.8VDC 2600mAh Li-ion	11.1VDC 2000mAh Li-ion
Rated Power	16 W		
Charger Input Voltage	100-240VAC 50/60Hz		
Battery Charging Time	~2hrs		
Non-Stop Running Time (Full Charge)	90 Min	90 Min	60 Min
Running Cycles (ON-OFF Cycles of 10 Seconds On Full Charge)	900	900	340
Stand-by Mode (Charge Hold relates to battery, not to the pump)	30 Days	30 Days	25 Days
Pump Service Life (Charge Hold)	100000+ ON-OFF cycles / 800+ hrs continuous action		
With Automatic OFF Switch	No	Yes	No
Rated Air Flow	0.7cfm (20 L/min)	0.7cfm (20 L/min)	0.5cfm (15 L/min)
Maximum Vacuum Rate	11.6Psi (0.8 Bar, 80 kPa)		
PHYSICAL LIMITATIONS			
Maximum Lifting Capacity	375Lbs (170 kg)	375Lbs (170 kg)	330Lbs (150 kg)
L x W x H	12.1 x 7.37 x 4.91" (297 x 181 x 121 mm)	12.1 x 7.37 x 4.91" (297 x 181 x 121 mm)	12.1 x 7.37 x 4.91" (297 x 181 x 121 mm)
Net Weight (With Battery)	3.3Lbs (1.6 kg)	3.2Lbs (1.5 kg)	2.6Lbs (1.2 kg)
Working Temperature	32°F~140°F (0°~60 °C)		
KIT			
Gauge Type	Mechanical With Protective Rubber Cover	Smart Digital Pressure Sensor	No Gauge
Number of Batteries	2	1	1
Charger	Multi Socket Charger		
Number of Seals	2 in Total	2 in Total	1 in Total
Warranty	1 Year Basic Warranty as outlined on WWW.THEGRABO.COM	1 Year Basic Warranty as outlined on WWW.THEGRABO.COM	1 Year Limited Warranty as outlined on WWW.THEGRABO.COM
Miscellaneous	Use for all surface types, without automatic stop function, without display and electronic pressure gauge	Use for all surface types, with automatic stop function at 11.6Psi, with digital display and electronic pressure gauge	Use for all surface types, with smaller battery, without automatic stop function, without display and pressure gauge, without strap eyelets